

High capacity shredders with feeding hopper

IDEAL 4605

Cutting width	6 MM	9 MM
Performance	90 – 100 SHEETS*	120 – 130 SHEETS*
Power connection**	400 VOLTS / 50 HZ / 3~	400 VOLTS / 50 HZ / 3~
Motor capacity	2.2 KW	2.2 KW
Feed opening	460 MM	460 MM
Security level	2	1
Dimensions (H x W x D)	1700 X 740 X 765 MM	1700 X 740 X 765 MM
Weight	256.0 KG	256.0 KG

IDEAL 4605-Cross/Cut

Particle size	2 X 15 MM	4 X 60 MM
Performance	35 – 40 SHEETS*	65 – 70 SHEETS*
Power connection**	400 VOLTS / 50 HZ / 3~	400 VOLTS / 50 HZ / 3~
Motor capacity	2.2 KW	2.2 KW
Feed opening	460 MM	460 MM
Security level	4	3
Dimensions (H x W x D)	1700 X 740 X 765 MM	1700 X 740 X 765 MM
Weight	256.0 KG	256.0 KG



CENTRALISED SHREDDING POWER FOR THE OFFICE FLOOR:

- tilting feeding hopper for crumpled paper
- second feed opening located under the hopper for flat paper and computer printouts with automatic start/stop via a photo cell
- fold-away feeding table
- front door and mobile shred bin for easy removal of the full shred bag
- high volume container of 230 litres for the shredded material
- soft touch keys for forward (continuous operation), stop and reverse
- optical indicators for the operational status of the machine
- main switch and emergency cut-off switch
- electronically controlled automatic reverse and power cut-off in case of overfeeding
- automatic stop when hopper or front door is opened, or when the shred bin is full
- robust shredding heads with special hardened cutting shafts made of high-grade steel, resistant against soft metal objects
- powerful three phase motor
- thermal motor protection
- mobile on castors



*paper A4, 70 g/m² **all common voltages available